
# Hybrid<sup>™</sup>E8 & E9

# All-in-One Ultraviolet Filtration with Reversible Bracket



\*Copper pipes (pictured) not included.





## Specifications

Note: All dimensions are in mm.

| Ordering Code | Pressure**<br>(kPa) | Max. Flow<br>(Lpm) | Connection              | Micron<br>Rating* |
|---------------|---------------------|--------------------|-------------------------|-------------------|
| HYBRID-E8-LF  | 300-875             | 75                 | 1" BSP(Male)<br>(25 mm) | 1                 |
| HYBRID-E9-LF  | 300-875             | 130                | 1" BSP(Male)<br>(25 mm) | 1                 |

Min/Max Temperature: 0-52°C. Protect from freezing.

### FILTRATION TECHNOLOGY

| Ordering Code        | Description       | Flow<br>(Lpm) | Micron Rating*<br>(Nominal) | Cartridge<br>Size |
|----------------------|-------------------|---------------|-----------------------------|-------------------|
| HYBRID-E8 CARTRIDGES |                   |               |                             |                   |
| PL20MP1              | Sediment          | 0-75          | 20                          | 10" MaxiPlus      |
| PX01MP1              | Polyspun Sediment | 0-90          | 1                           | 10" MaxiPlus      |
| HYBRID-E9 CARTRIDGES |                   |               |                             |                   |
| PL20MP2              | Sediment          | 0-130         | 20                          | 20" MaxiPlus      |
| PX01MP2              | Polyspun Sediment | 0-180         | 1                           | 20" MaxiPlus      |

#### HYBRIDCARE SERIES MAINTENANCE KIT

| Ordering Code | Components  |
|---------------|---|
| HR-EI8        | Includes: 10" MaxiPlus™ Pleated Sediment Cartridge<br>[PL20MP1], Polyspun Sediment Cartridge [PX01MP1], 46W<br>UV Lamp [RL7], and Replacement Quartz Sleeve [RQS6]. |
| HR-EI9        | Includes: 20" MaxiPlus™ Pleated Sediment Cartridge<br>[PL20MP2], Polyspun Sediment Cartridge [PX01MP2], 46W<br>UV Lamp [RL7], and Replacement Quartz Sleeve [RQS6]. |

Warranty: Use only genuine Puretec replacement cartridges. 3 year warranty is 1 year parts and labour, 2 years parts only. Excludes cartridges.







Warning: Please visit www.puretecgroup.com/instructions to observe essential manufacturer's instructions before use. Note: No claims can be made based on the specifications and images in this document. The design, technology, colours, features and prices are subject to change. This document and all its contents are copyright protected. All rights are reserved, particularly alteration, translation and reproduction using electronic systems. This spec sheet has been designed to help make product selection easy. However due to the complex nature of water chemistry, we strongly encourage confirming any product selection with one of our team. We may need to perform a water analysis test to confirm contaminants in water. Caution: Do not use with microbiologically unsafe water or water of unknown quality without adequate disinfection before or after the system. Warrantty: "Warranties in this document cover parts for the period stated and include cover for parts and abour for the first year where applicable, subject to approval. Excludes consumables. "Micron Rating is nominal. Our Water Filtration Specialists can provide you with advice to suit your needs." "Where line pressure exceeds S20kPa, an approved pressure limiting device must be installed to comply with Australian & New Zealand Plumbig Standards (Ref. AS 550012021, Clause 3.5.4). Maximum flow depends on cartridges, vessel, pressure, impurities etc.

