

Z1-MW-K


Quick Twist Undersink Water Filter System Kit




MAINS WATER



Parts Included



User guide



Note: All dimensions are in mm.

Specifications

| Ordering Code | Temp °C | Pressure** (kPa) | Flow (Lpm) | Micron Rating* | Connection | Cartridge Size | Capacity*** (L) |
|---------------|---------|------------------|------------|----------------|----------------------|----------------|-----------------|
| Z1-MW-K | 0-38 | 200-520 | 5.5 | 0.1 | 1/2" BSP x 1/4" Tube | 10" | 30,000 |

Notes: Designed for low sediment mains or town water applications. Connects to any mixer tap. Unit can be installed vertically or horizontally. Protect from freezing.

Replacement Cartridge: Z1-R. No tap included.

Z PLUS FILTRATION TECHNOLOGY

| | |
|---------|---|
| STAGE 1 | <ul style="list-style-type: none"> Removes* particles Clarifies the water Removes* sediment, rust, sand, silt and algae |
| STAGE 2 | <ul style="list-style-type: none"> Chlorine and chloramine reduction Eliminates* bad taste and odours Chemical pesticides and sulphur reduction |
| STAGE 3 | <ul style="list-style-type: none"> Ultra Z Filtration membrane finely filters to 0.1 micron* Provides protection against cysts and bacteria such as E. coli Removes the finest particles |

Warranty:

Use only genuine Puretec replacement cartridge. 10 year warranty[^] is 1 year parts and labour, 9 years parts only.



Warning: Please visit www.puretec.com.au/instructions to observe essential manufacturer's instructions before use. **Note:** No claims can be made based on the specifications and images in this document. The design, technology, colours, features and prices are subject to change. This document and all its contents are copyright protected. All rights are reserved, particularly alteration, translation and reproduction using electronic systems. This spec sheet has been designed to help make product selection easy. However due to the complex nature of water chemistry, we strongly encourage confirming any product selection with one of our team. We may need to perform a water analysis test to confirm contaminants in water. **Caution:** Do not use with microbiologically unsafe water or water of unknown quality without adequate disinfection before or after the system. Our Water Filtration Specialists can provide you with advice to suit your needs. **Where line pressure exceeds 520kPa, an approved pressure limiting device must be installed to comply with Australian & New Zealand Plumbing Standards. (Ref. AS 3500:2021, Clause 3.3.4). Maximum flow depends on cartridges, vessel, pressure, impurities etc. *Micron rating is nominal. ***Capacity is based on inlet chlorine @2ppm ±10%. *The term 'removal' and 'eliminate' indicates significant reduction, not necessarily 100% removal.